



INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Stairwell LED Series



WareLight's stairwell LED lights combine cutting-edge LED technology with sleek and modern designs. Our stairwell light is CCT and wattage selectable, available in 2-foot and 4-foot lengths and are designed to be wall mounted. Ideal for residential, commercial, and institutional settings, they are suitable for a wide range of applications. Illuminate hallways, corridors, stairwells, and entryways with confidence, knowing that our lights will provide reliable performance in any environment.

Specifications

CRI	82	Ratings & Certifications	DLC Premium, cULus, Damp Location
Light Source	Integrated LED	Beam Angle	Wide
Dimmable	0-10v	Linkable	Continuous Run Available
Color Temperature	Selectable 3500K - 4000K - 5000K	Mounting Options	Wall Mounted (mounting kit included)
Wattage	Selectable 10W-40W	Operating Temperature	-30 ~ 40 °C (-22°F to +104°F)
LPW	115/w	Lumens	1,150-4,600lm
Voltage	120-277v	Lens	Milky Lens
Finish	White	Warranty	5 Years





INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Order Information

LED Corridor Light Series			Example: WL-SWLED2-20W-CWS-WH-MS		
Series	Length	Wattage	Color Temperature	Finish	Accessories*
WL-SWLED	2 2 Foot	20W 10W/15W/20W	CWS 35K/40K/50K	WH White	MS Motion Sensor
	4 4 Foot	40W 20W/30W/40W			EM Emergency Battery Backup

*Accessories Sold Separately

Motion Sensor (MS)



Emergency Battery Backup (EM)



Performance Chart

Model Number	Size	Wattage	Lumens	Efficacy	CRI
WL-SWLED2-20W-CWS-WH	2 FT	10W/15W/20W	1,150-2,320	115 LM/W	82
WL-SWLED4-40W-CWS-WH	4 FT	20W/30W/40W	2,320-4,600	115 LM/W	82

Dimensions

Item	Length	Width	Height	Weight
WL-SWLED2-20W-CWS-WH	24.02"	3.66"	3.54"	lbs.
WL-SWLED4-40W-CWS-WH	48.03"	3.66"	3.54"	lbs.

