



INDUSTRIAL AND COMMERCIAL  
LIGHTING MFR SINCE 2003

PROJECT NAME \_\_\_\_\_  
ITEM # \_\_\_\_\_  
FIXTURE SCHEDULE \_\_\_\_\_  
NOTES \_\_\_\_\_

# Narrow Strip Light Series



Featuring a slim design, this linear strip light combines high-quality housing with precision optics to create a sleek and subtle aesthetic. Perfectly suited for various office ceiling applications, it seamlessly integrates into any space. Ideal for office spaces, supermarkets, meeting rooms, and workshops, this light offers both functionality and style. The 8 Foot fixture ships in two 4-foot sections and uses a rigid linking bracket to connect the sections.

## Specifications

|                            |                                                                                             |                       |                      |
|----------------------------|---------------------------------------------------------------------------------------------|-----------------------|----------------------|
| CRI                        | >80                                                                                         | Dimmable              | 0-10V                |
| Light Source               | LED                                                                                         | Mounting              | Surface or Suspended |
| CCT                        | Selectable 3000K/4000K/5000K                                                                | Operating Temperature | (-40°C) TO 40°C      |
| Wattage                    | Selectable 7W-70W                                                                           | Housing               | Steel                |
| LPW                        | 129 LPW                                                                                     | Voltage               | 120-277v             |
| Lumens                     | 2,580-8,700                                                                                 | Finish                | White                |
| Ratings and Certifications | UL and CUL listed, DLC Premium<br>DLC IDs: 2FT - S-Y38FZJ / 4FT - S-H04GIE / 8FT - S-5EDGYZ | Warranty              | 5 Years              |

*\*Data is considered to be representative of the series. Actual production may vary between up to ±10% of initial delivered lumens.*






INDUSTRIAL AND COMMERCIAL  
LIGHTING MFR SINCE 2003

PROJECT NAME \_\_\_\_\_  
ITEM # \_\_\_\_\_  
FIXTURE SCHEDULE  
NOTES \_\_\_\_\_

## Order Information

| Narrow Strip Light Series |                    |                                          |                                                 | Example: WL-NLS2-CW20T-DMV-G2            |            |                                                                             |
|---------------------------|--------------------|------------------------------------------|-------------------------------------------------|------------------------------------------|------------|-----------------------------------------------------------------------------|
| Series                    | Length             | Wattage                                  | CCT                                             | Voltage/Dimming                          | Generation | Mounting                                                                    |
| WL-NLS                    | <b>2</b><br>2 Foot | <b>C20W</b><br>7W/14W/20W<br>Selectable  | <b>T</b><br>CCT Selectable<br>3000K/4000K/5000K | <b>DMV</b><br>120-277V<br>0-10V Dimmable | <b>G2</b>  | <b>Blank</b><br>Surface Mount<br><br><b>3CHK</b><br>3' Hanging Chain<br>Kit |
|                           | <b>4</b><br>4 Foot | <b>C45W</b><br>22W/33W/45W<br>Selectable |                                                 |                                          |            |                                                                             |
|                           | <b>8</b><br>8 Foot | <b>C20W</b><br>33W/50W/69W<br>Selectable |                                                 |                                          |            |                                                                             |

## Mount Options



## Performance Chart

| Model Number         | Wattage     | Lumens | Efficacy | CRI |
|----------------------|-------------|--------|----------|-----|
| WL-NLS2-C20WT-DMV-G2 | 7W/14W/20W  | 2,580  | 129 LM/W | >80 |
| WL-NLS4-C45WT-DMV-G2 | 22W/33W/45W | 5,500  | 123 LM/W | >80 |
| WL-NLS8-C70WT-DMV-G2 | 33W/50W/69W | 8,700  | 126 LM/W | >80 |




INDUSTRIAL AND COMMERCIAL  
LIGHTING MFR SINCE 2003

PROJECT NAME \_\_\_\_\_  
ITEM # \_\_\_\_\_  
FIXTURE SCHEDULE \_\_\_\_\_  
NOTES \_\_\_\_\_


## Dimensions

| Item                 | Length | Width | Height | Weight   |
|----------------------|--------|-------|--------|----------|
| WL-NLS2-C20WT-DMV-G2 | 24.1"  | 2.65" | 3.03"  | 1.96 lbs |
| WL-NLS4-C45WT-DMV-G2 | 47.8"  | 2.65" | 3.03"  | 2.33 lbs |
| WL-NLS8-C70WT-DMV-G2 | 96"    | 2.65" | 3.03"  | 4.30 lbs |

### WL-NLS2



### WL-NLS4



### WL-NLS8

