



INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Beam Pendant Direct Series



This 24" round linear pendant brings another style to our linear architectural family. This fixture is ideal for small seating areas and tables in commercial buildings, schools/libraries, reception areas and conference rooms. There are 4 color temperature options, field selectable. It is available in white or black finishes and can be pendant mounted.

Specifications

CRI	>82	Ratings & Certifications	cULus, Damp Location
Light Source	Integrated LED	Beam Angle	Wide
Voltage	120-277V	Dimmable	0-10v
Color Temperature	3000K - 3500K - 4000K - 5000K	Mounting Options	Suspended
Wattage	20W/30W/40W	Operating Temperature	-30° C to 40° C (-22° F to 104° F)
LPW	80-100	Lumens	3200 - 4000
Housing	Extruded Aluminum	Finish	Black or White
Product Weight	9.92 lbs	Product Dimensions	23.62" Diameter x 3.15" Height
Shipping Weight	11.02 lbs	Shipping Dimensions	24.4" L x 24.8" W x 3.93" H
Lifespan	50,000+	Warranty	5 Years

*Data is considered to be representative of the series. Actual production may vary between up to ±10% of initial delivered lumens.





INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Order Information

Architectural Pendant Round			Example: BEAMPEND-24-4C40WS-BK-G2		
Series	Diameter	CCT	Wattage	Finish	Generation
BEAMPEND	24 24" Round	4CT 3000K/3500K/4000K/5000K	40W Select 20W/30W/40W	BK Black WH White	G2

Dimensions

Item	Diameter	Height	Weight
BEAMPEND-24-4CT-40W-BK-G2	23.62"	3.15"	9.92 lbs.
BEAMPEND-24-4CT-40W-WH-G2	23.62"	3.15"	9.92 lbs.

