



INDUSTRIAL AND COMMERCIAL  
LIGHTING MFR SINCE 2003

PROJECT NAME \_\_\_\_\_  
ITEM # \_\_\_\_\_  
FIXTURE SCHEDULE \_\_\_\_\_  
NOTES \_\_\_\_\_

# Static UFO High Bay Series



These high performing, high bay lights are an energy-efficient replacement for traditional HID fixtures with mounting heights ranging from 15' to 40' depending on wattage and application. These fixtures are instant on and give you the freedom to control the brightness with 0-10V dimming. They are widely used in warehouses, cold storage facilities, workshops, convention centers, retail stores, gymnasiums, factories, and other industrial and commercial indoor areas.

## Specifications

CRI	>80	Ratings and Certifications	UL, IP65, DLC Premium v5.1
Light Source	LED	Dimmable	0-10V
Voltage	120-277V	Beam Angle	110°
Color Temperature	5000K	Mounting Options	Hook, Pendant, Bracket
Wattage	100W, 150W, 200W	Operating Temperature	40°C - +50°C (-40°F - +122°F)
LPW	150	Lumens	15,000-30,000
Housing	Die-cast Aluminum	Finish	Black
Lifespan	50,000	Warranty	5 Year





INDUSTRIAL AND COMMERCIAL  
LIGHTING MFR SINCE 2003

PROJECT NAME \_\_\_\_\_  
ITEM # \_\_\_\_\_  
FIXTURE SCHEDULE \_\_\_\_\_  
NOTES \_\_\_\_\_

## Order Information

Saturn Series			Example: WL-SUFO-100W-50K-UNV-BK	
Series	Wattage	CCT	Voltage	Color
WL-SUFO	100W 150W 200W	<b>50K</b> 5000K	<b>UNV</b> 120-277V	<b>BK</b> Black

## Accessories

### Mounting Bracket, Black or White

WL-BT-BRT-PA-BK-G3 / WL-BT-BRT-PA-WH-G3



### Emergency Battery Backup

WL-LECV-UFO-40D-R-G3



### EM Remote

WL-BT-RC-EM



### Conduit Boxes

CondMT-BK / CondMT-WH



## Performance Chart

Item	Wattage	Lumens	Efficacy	CRI
WL-SUFO-100W-50K-UNV-BK	100W	15,000	150 LM/W	>80
WL-SUFO-150W-50K-UNV-BK	150W	22,500	150 LM/W	>80
WL-SUFO-200W-50K-UNV-BK	200W	30,000	150 LM/W	>80

## Dimensions

Item	Height	Diameter	Weight
WL-SUFO-100W-50K-UNV-BK	6.97"	9.89"	3.41 lbs.
WL-SUFO-150W-50K-UNV-BK	6.97"	9.89"	3.41 lbs.
WL-SUFO-200W-50K-UNV-BK	7.29"	11.07"	3.95 lbs.