

PROJECT NAME
ITEM #
FIXTURE SCHEDULE
NOTES

WL-PLF G3 Series



The Quasar G3 LED Area/Parking Lot lighting fixture is applicable for both commercial and residential illumination at the places where you need a large amount of light such as parking lots, driveways, outdoor courts (basketball, tennis, volleyball, etc.).

Specifications – 300W

CRI	>80	Surge	10kV
Light Source	LED	Housing	Die-cast Aluminum
Dimmable	1-10V	Mount	Adjustable Slipfitter
ССТ	5000K	Operating Temperature	-40° C to 45° C (-40° F to 104° F)
Wattage	300W	Optic	Type 3 or Type 5
LPW	133	Voltage	120-277
Finish	Bronze	Warranty	5 Years
Ratings	cULus, IP65		

^{**} Data is considered to be representative of the series. Actual production may vary between up to $\pm 10\%$ of initial delivered lumens.










PROJECT NAME
ITEM #
FIXTURE SCHEDULE
NOTES


Order Information

Area Light Quasar Gen 3			Example: WL-PLF-150W-40K-T3-B-ASF-MV-G3				
Fixture Type	Wattage	ССТ	Optic	Finish	Mount	Voltage	Generation
WL-PLF	100W 100 Watts 150W 150 Watts 300W 300 Watts	40K 4000 (40K only available in 150W) 50K 5000K	T3 Type 3 (ISOW T3 in 4000K only) T5 Type 5	B Bronze	ASF Adjustable Slipfitter APM Round/Square Pole Mount AYM Adjustable Yoke Mount	MV Universal Voltage 120-277V	G3 Generation 3


DLC Information

Item	DLC Version	DLC ID	Wattage	Lumens*
WL-PLF-100W-50K-T5-B-ASF-MV-G3	5.1P	S-ZOXJD1	100	13582
WL-PLF-100W-50K-T3-B-ASF-MV-G3	5.1P	S-9HNBW8	100	13403
WL-PLF-150W-40K-T3-B-ASF-MV-G3	5.1P	S-ZE6PBT	150	19059
WL-PLF-150W-50K-T3-B-ASF-MV-G3	5.1P	S-C0TN7O	150	19582
WL-PLF-150W-50K-T5-B-ASF-MV-G3	5.1P	S-6PUX80	150	19857
WL-PLF-300W-50K-T3-B-ASF-MV-G3	5.1P	S-4OSYLF	300	40473
WL-PLF-300W-50K-T5-B-ASF-MV-G3	5.1P	S-BEO32X	300	41066





WL-PLF-100W/150W



WL-PLF-300W

