

# WL-TRCBLED TAA Series



WareLight's LED Volumetric Troffer is a high-efficiency lighting solution delivering up to 130 lm/W, featuring field-selectable wattage and adjustable CCT for maximum versatility across applications. Designed for 120–277V operation, it includes 0–10V dimming for enhanced energy control and visual comfort. Its TAA compliance makes it an ideal choice for government and federally funded projects requiring adherence to Trade Agreements Act standards.

## Specifications

CRI	≥ 80	LED Lifespan	50,000 hours
Light Source	LED	Dimmable	0-10V
Voltage	120-277V	Operating Temp	-20°C to 50°C
CCT	30/35/40/50/60K	Mounting Options	Drop Ceiling
Wattage	20W-72W	Beam Angle	120°
Lumens*	2600-9360Lm	Finish	White
LPW	130 Lm/W	Certifications	ETL Listed, TAA Compliant, DLC Pending
Housing	Steel		

\*Data is considered to be representative of the series. Actual production may vary between up to ±10% of initial delivered lumens.



## Order Information

WL-TRCBLED TAA Series			Example: WL-TRCBLED-2x2-40W-5WS-5CCT-DM010-TAA		
Series	Length	Wattage	Color Temperature	Dimming	Compliance
<b>WL-TRCBLED</b> Troffer Center Basket Series	<b>2x2</b>	<b>40W-5WS</b> 20/25/30/35/40W Selectable	<b>5CCT</b> 30/35/40/50/60K Selectable	<b>DM010</b> 0-10V Dimmable	<b>TAA</b> Trade Agreements Act
	<b>2x4</b>	<b>72W-5WS</b> 30/40/50/60/72W Selectable			

## Performance Chart

Item	Wattage	Lumens	Efficacy	CRI
WL-TRCBLED-2x2-40W-5WS-5CCT-DM010-TAA	20/25/30/35/40W	2600/3250/3900/4550/5200	130 LM/W	>80
WL-TRCBLED-2x4-72W-5WS-5CCT-DM010-TAA	30/40/50/60/72W	3900/5200/6500/7800/9360	130 LM/W	>80

## Dimensions

Item	Length	Width	Height	Weight
WL-TRCBLED-2x2-40W-5WS-5CCT-DM010-TAA	23.74"	23.74"	2.09"	5.95 lbs
WL-TRCBLED-2x4-72W-5WS-5CCT-DM010-TAA	47.72"	23.74"	2.09"	7.27 lbs