



INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Bullet Flood Light Series



WareLight's compact but powerful bullet flood light is a true innovation, both practically and aesthetically. Now featuring optic selectability, this fixture offers enhanced versatility to suit a wide range of applications. The upgraded tuning switch allows for easy access to multiple CCTs and wattage options, adapting seamlessly to different environments. Utilizing high-performance optics and a long-lasting driver, these landscape flood lights are built to deliver reliable performance for years to come.

Specifications

| | | | |
|----------------------------|--|-----------------------|----------------------|
| CRI | >80 | Beam Angle | Selectable 25/45/65° |
| Light Source | LED | Mounting | 1/2" Knuckle |
| CCT | Selectable 3000K/4000K/5000K | Operating Temperature | (-40°C) TO 40°C |
| Wattage | Selectable 9W/16W/24W | Housing | Die-Cast Aluminum |
| LPW | 144 LPW | Voltage | 120-277v |
| Lumens | 1297/2304/3456 Lm | Finish | Bronze |
| Ratings and Certifications | UL and CUL listed for wet locations, DLC Premium | Warranty | 5 Years |

**Data is considered to be representative of the series. Actual production may vary between up to ±10% of initial delivered lumens.*





INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Order Information

| Bullet Flood Light Series | | Example: WL-BFL-24W-3WS-3CCT-3OPT-BZ-PC-G2 | | | | |
|---------------------------|--|--|--|----------------------------|--------------------------------------|---------------------------|
| Series | Wattage | Color Temperature | Optic | Housing | Photocell | Generation |
| WL-BFL | 24W-3WS 9W/16W/24W Selectable | 3CCT 30K/40K/50K Selectable | 3OPT 25/45/65° Selectable | BZ Bronze Finish | PC Integrated Photocell | G2 Generation 2 |

Performance Chart

| Model Number | Wattage | Lumens | Efficacy | CRI |
|-----------------------------------|------------|-------------------|----------|-----|
| WL-BFL-24W-3WS-3CCT-3OPT-BZ-PC-G2 | 9W/16W/24W | 1297/2304/3456 Lm | 144LM/W | >80 |

Dimensions

| Item | Length | Width | Height |
|-----------------------------------|--------|-------|--------|
| WL-BFL-24W-3WS-3CCT-3OPT-BZ-PC-G2 | 7.24" | 5.9" | 8.74" |

