



INDUSTRIAL AND COMMERCIAL  
LIGHTING MFR SINCE 2003

PROJECT NAME \_\_\_\_\_  
ITEM # \_\_\_\_\_  
FIXTURE SCHEDULE \_\_\_\_\_  
NOTES \_\_\_\_\_

# LED Flood Light Series



WareLight's LED Flood Lights offer exceptional performance and flexibility for a wide range of outdoor lighting applications. Each model features selectable wattage, color temperature, and beam optics, allowing for customized illumination to suit your needs. Built for convenience and efficiency, these fixtures include an integrated photocell for automated dusk-to-dawn operation and offer versatile installation with multiple mounting options.

## Specifications

CRI	>80	Beam Angle	7H6V / 6H6V / 5H5V Selectable
Light Source	Lumileds SMD2835 LED	Dimmable	0-10V
CCT	3000K/4000K/5000K Selectable	Mounting	Knuckle, Trunnion, Yoke, Slipfitter
Wattage	15W-320W Selectable	Operating Temperature	-40°C to +50°C
LPW	150 LPW	Housing	Die-Cast Aluminum
Lumens	2,250-48,000 Lm	Voltage	120-277VAC, 50/60Hz
Lifespan	50,000 Hrs	Finish	Bronze
Ratings and Certifications	UL/cUL Listed, DLC 5.1 Premium, IP65	Warranty	5 Years





INDUSTRIAL AND COMMERCIAL  
LIGHTING MFR SINCE 2003

PROJECT NAME \_\_\_\_\_  
ITEM # \_\_\_\_\_  
FIXTURE SCHEDULE \_\_\_\_\_  
NOTES \_\_\_\_\_

## Order Information

Flood LED Series		Example: WL-FLLED-60W-3WS-3CCT-3OPT-DM010-BZ		
Series	Wattage	Color Temperature	Optic	Dimming
<b>WL-FLLED</b> Flood LED Series	<b>35W-3WS</b> 15/25/35W Selectable	<b>3CCT</b> 3000/4000/5000K Selectable	<b>3OPT</b> 7H6V/6H6V/5H5V Selectable	<b>DM010</b> 0-10V Dimmable
	<b>60W-3WS</b> 40/50/60W Selectable			
	<b>150W-3WS</b> 100/120/150W Selectable			
	<b>320W-3WS</b> 200/240/320W Selectable			

\*Includes Photocell

## Mounting Options

Model Number	Description
FLLED-KN-S	1/2" Knuckle for 35W-60W (Included on 35W and 60W Model)
FLLED-TR-S	Trunnion for 35W-60W
FLLED-SF-L/XL	Slipfitter for 150W and 320W (Included on 150W and 320W Model)
FLLED-YK-L	Yoke for 150W
FLLED-YK-XL	Yoke for 320W

## Performance Chart

Model Number	Wattage	Lumens	Efficacy	CRI
WL-FLLED-35W-3WS-3CCT-3OPT-DM010-BZ	15/25/35W	2,250/3,750/5,250Lm	150 LM/W	>80
WL-FLLED-60W-3WS-3CCT-3OPT-DM010-BZ	40/50/60W	6,000/7,500/9,000Lm	150 LM/W	>80
WL-FLLED-150W-3WS-3CCT-3OPT-DM010-BZ	100/120/150W	15,000/18,000/22,500Lm	150 LM/W	>80
WL-FLLED-320W-3WS-3CCT-3OPT-DM010-BZ	200/240/320W	30,000/36,000/48,000Lm	150 LM/W	>80



INDUSTRIAL AND COMMERCIAL  
LIGHTING MFR SINCE 2003


PROJECT NAME \_\_\_\_\_  
ITEM # \_\_\_\_\_  
FIXTURE SCHEDULE \_\_\_\_\_  
NOTES \_\_\_\_\_

## Dimensions

Item	Length	Width	Height	Weight
WL-FLLED-35W-3WS-3CCT-3OPT-DM010-BZ	7.80"	8.80"	3.15"	3.26 lbs.
WL-FLLED-60W-3WS-3CCT-3OPT-DM010-BZ	9.76"	9.74"	3.62"	4.80 lbs.
WL-FLLED-150W-3WS-3CCT-3OPT-DM010-BZ	12.51"	14.22"	5.57"	10.71 lbs.
WL-FLLED-320W-3WS-3CCT-3OPT-DM010-BZ	16.35"	17.00"	6.74"	17.24 lbs.

### WL-FLLED-35W


#### 1/2'Knuckle



#### Trunnion




#### YokeMount




### WL-FLLED-60W


#### 1/2'Knuckle



#### Trunnion




#### YokeMount




### WL-FLLED-150W


#### Slipfitter



#### Trunnion




#### YokeMount




### WL-FLLED-320W

#### Slipfitter



#### Trunnion



#### YokeMount

