



INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Aries G6 UFO High Bay Series



The Aries G6 LED UFO High Bay Series provides high-performance, flexible lighting for warehouses and industrial spaces, featuring selectable wattage options, selectable CCT, and selectable beam angles to cover a wide range of applications with a single fixture. They are sensor ready for easy controls integration and available in black or white housing for a clean, professional finish.

Specifications

CRI	>80	Ratings and Certifications	UL, IP65, DLC Premium v5.1
Light Source	LED	Dimmable	0-10V Dim to Off
Voltage	120-277	Beam Angle	3-in-1 Optic 60/80/100°
Color Temperature	Select 3500K/4000K/5000K	Mounting Options	Hook, Stem, Bracket
Wattage	Select 100W-240W	Operating Temperature	-40°C - +50°C (-40°F - +122°F)
LPW	150	Lumens	15,000-36,000
Housing	Die-cast Aluminum	Finish	Black/White
Lifespan	50,000	Warranty	5 Year





INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Order Information

Aries IUFO		Example: WL-IUFO-150W-3WS-3CCT-3OPT-DM010-BK-G6				
Series	Wattage & Color Temperature		Optic	Dimming	Finish	Accessories
WL-IUFO	150W-3WS 100W/120W/150W	3CCT 35K/40K/50K	3OPT 3-in-1 Optic 60/80/100°	DM010 0-10V Dimmable	BK Black WH White	PIR PIR Sensor
	240W-3WS 150W/200W/240W					MWS Microwave Sensor
						BMS Bluetooth Motion Sensor

Accessories

Yoke Mount, Black or White



IUFO-150W-YOKE-[BK,WH]
IUFO-240W-YOKE-[BK,WH]

1/2" or 3/4" Conduit Boxes, Black or White



IUFO-CONDBOX-1/2-[BK,WH]
IUFO-CONDBOX-3/4-[BK,WH]

Emergency Battery Backup



WL-LECV-UFO-40D-R-G3

Emergency Remote



WL-BT-RC-EM

PIR Sensor



ANT-6-4T

Microwave Sensor



ANT-5-4T

Sensor Remote



RC-100

Reflectors



Prismatic



Aluminum



Black



INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Performance Chart

Item	Wattage	Lumens	Efficacy	CRI
WL-IUFO-150W-3WS-3CCT-3OPT-DM010-[BK,WH]-G6	100W/120W/150W	15,000/18,000/22,500	150 LM/W	>80
WL-IUFO-240W-3WS-3CCT-3OPT-DM010-[BK,WH]-G6	150W/200W/240W	30,000/33,000/36,000	150 LM/W	>80

Dimensions

Item	Height	Diameter
WL-IUFO-150W-3WS-3CCT-3OPT-DM010-[BK,WH]-G6	7.8"	11.90"
WL-IUFO-240W-3WS-3CCT-3OPT-DM010-[BK,WH]-G6	7.8"	14.20"

