

# WL-STLED Series



Maximize flexibility and performance with WareLight's LED Strip Lights, designed for high-efficiency lighting in commercial, industrial, and warehouse environments. This versatile fixture offers five selectable wattages and color temperatures making it ideal for a range of applications and lighting preferences. Delivering up to 150 lumens per watt, this strip light ensures powerful, energy-efficient illumination. Plus, it's sensor-ready, compatible with a wide range of occupancy and daylight sensors, making it perfect for smart lighting systems and energy-saving projects.

## Specifications

CRI	>80	Ratings and Certifications	cUL, DLC 5.1
Light Source	LED	Voltage	120-277V
Dimmable	0-10V	Beam Angle	120°
CCT	35/40/50/57/65K	Mounting Options	Surface mount or suspended
Wattage	12-80W	Operating Temperature	-4°F to 113°F
LPW	150	Housing	Metal
Lumens	1,800-12,000	Warranty	5 Years
Lifespan	50,000		



## Order Information

WL-STLED Series		Example: WL-STLED4-40W-5WS-5CCT-DM010				
Series	Size/Length	Wattage	Color Temperature	Dimming	Mounting	Controls
<b>WL-STLED</b> Industrial Strip Light	<b>4</b> 4 Foot	<b>40W-5WS</b> 12/25/30/35/40W Selectable	<b>5CCT</b> 35/40/50/57/65K Selectable	<b>DM010</b> 0-10V Dimmable	<b>blank</b> Standard Surface Mount	<b>MS</b> PIR Motion Sensor
	<b>8</b> 8 Foot	<b>80W-5WS</b> 24/30/50/64/80W Selectable			<b>SMC</b> J-Box Cover - Surface Mount Kit	
					<b>S-KIT</b> 5' Suspension Kit	<b>BMS</b> WareSense Blue - Bluetooth Motion Sensor

## Mount Options

Part #	Description
(blank)	Installs directly to surface through fixture body.
STLED-SMC	Surface Mount Kit and J-Box Cover for WL-STLED Series.
STLED4-S-KIT	5' Adjustable Suspension Kit for WL-STLED4 Series
STLED8-S-KIT	5' Adjustable Suspension Kit for WL-STLED8 Series
STLED-EM-8W	8W Emergency Battery Backup for WL-STLED Series

## Performance Chart

Item	Wattage	Lumens	Efficacy	CRI
WL-STLED4-40W-5WS-5CCT-DM010	12/25/30/35/40W	1800/3750/4500/5250/6000	150 LM/W	>80
WL-STLED8-80W-5WS-5CCT-DM010	24/30/50/64/80W	3600/4500/7500/9600/12000	150 LM/W	>80

## Dimensions

Item	Length	Width	Height	Weight
WL-STLED4-40W-5WS-5CCT-DM010	48"	2.95"	3.26"	3.3 lbs.
WL-STLED8-80W-5WS-5CCT-DM010	96"	3.35"	3.56"	6.86 lbs.