




INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

LED Vapor Tight High Bay



WareLight's 4FT LED Vapor Tight High Bay delivers powerful, energy-efficient lighting with selectable wattage and color temperature, allowing you to customize output and light appearance on-site. Producing up to 29,000 lumens at 130 lumens per watt, this fixture is ideal for warehouses, manufacturing facilities, parking garages, and other high-ceiling applications. Designed for durability, it features an IP65 rating for protection against dust and moisture and an IK08 impact rating for added toughness. Built for demanding environments, it provides reliable, high-performance illumination with simple installation and long-term efficiency.

Specifications

CRI	>80	Beam Angle	120°
Light Source	LED	Mounting	Surface or Suspended
Dimmable	0-10V	Operating Temperature	-4°F - 113°F
CCT	Selectable 3500K/4000K/5000K	Housing	Plastic
Wattage	Selectable 160/180/200W	Voltage	120V-277V
LPW	145 Lm/W	Finish	White
Lumens	23,200/26,100/29,000	Warranty	5 Years
Ratings and Certifications	IP65, ETL, IK08		





INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Order Information

LED Vapor Tight High Bay		Example: WL-VTHB-200W-3WS-3CCT-DM010	
Series	Wattage	Color Temperature	Dimmable
WL-VTHB Vapor Tight High Bay	200W-3WS Selectable 160/180/200W	3CCT Selectable 3500K/4000K/5000K	DM010 0-10V Dimmable

Performance Chart

Model Number	Wattage	Lumens	Efficacy	CRI
WL-VTHB-200W-3WS-3CCT-DM010	160/180/200W	23,200/26,100/29,000	145 LM/W	>80

Dimensions

Item	Length	Width	Height	Weight
WL-VTHB-200W-3WS-3CCT-DM010	47.24"	10.24"	4.53"	13.78 lbs.

